

General Specifications



Model CCB1 CT-signal Transmitter (RMS-computing Type)

SMPSC

General

The CCB1 is a compact, plug-in CT-signal transmitter that converts AC current signal from a current transformer (CT) into isolated DC voltage or DC current signals.

Model and Suffix Codes



Input/Output Specifications

Type of input: 0 to 1 or 0 to 5A AC signal
 Input loss: 0.5 VA maximum
 Input frequency range: 40 Hz to 10kHz
 Maximum allowable overrange input:
 120% (continuous); 500% (for five seconds)
 Output signal: DC voltage or DC current
 Allowable load resistance:

Output-1 Range	Allowable Load Resistance	Output-1 Range	Allowable Load Resistance
4 to 20 mA DC	750 max.	0 to 10 mV DC	250K min.
2 to 10 mA DC	1500 max.	0 to 100 mVDC	250K min.
1 to 5 mA DC	3000 max.	0 to 1 V DC	2K min.
0 to 20 mA DC	750 max.	0 to 10 V DC	10K min.
0 to 16 mA DC	900 max.	0 to 5 V DC	2K min.
0 to 10 mA DC	1500 max.	1 to 5 V DC	2K min.
0 to 1 mA DC	15K max.	-10 to +10V DC	10K min.

Zero and span adjustment : Within ±5% of span for both zero and span adjustment



Standard Performance

Accuracy rating: $\pm 0.5\%$ of span; accuracy is not guaranteed for output levels less than 0.5% of the span of a 0 to X mA output range type.

Response speed: 175ms for a 63% response (10 to 90% change of range)

Effects of power line regulation: Up to $\pm 0.1\%$ of span for the regulation within allowable range of each supply voltage range.

Effects of ambient temperature variations: Up to $\pm 0.2\%$ of Span per 10

Conformance to EMC Standards

Applicable EMC standard: EN61326

CE-certified models mean those which are CE certified on condition that they be operated over a supply voltage range of 15~30 V DC ($\pm 20\%$) only.

Power Supply and Isolation

Supply rated voltage range: 100-240 V AC/DC 50/60Hz or 15-30 V DC

Supply input voltage range: 100-240 V AC/DC (-15, +10%) 50/60Hz or 15-30 V DC ($\pm 20\%$)

Power consumption: 2.2W at 24V DC; 2.1W at 110 V DC; 4.2 VA at 100V AC; 6.1VA at 200 V AC

Insulation resistance: 100 M minimum at 500V DC between input, output-1, power supply and grounding terminals mutually

Withstanding voltage: 2000 V AC for one minute between input, (output-1), power supply and grounding terminals mutually; 1000 V AC for one minute between output-1

Environmental Conditions

Operating temperature range: 0 to 50

Operating humidity range: 5 to 90% RH (no condensation)

Operating conditions: Avoid installation in such environments as corrosive gas like sulfide hydrogen, dust, sea breeze and direct sunlight.

Installation altitude: 2000 m or less above sea level.

Mounting and Appearance

Material: ABS resin (casing)

Mounting method: Wall or DIN rail mounting

Connection method: M3 screw terminals

External dimensions: 76(H) \times 29.5(W) \times 124.5(D) mm (including a socket)

Weight: Approx. 122g (main unit), approx. 51g (socket)


Customized Signal Specifications

Table 1. Manufacturable Ranges

	Current Signal	Voltage Signal
Input range (AC)	0 to 5 A	—
Span (AC)	0.1A to 5A	—
Zero elevation	0 % only	—
Output range (DC)	0 to 24 mA	-10 to +10 V
Span (DC)	1 to 24 mA	10mV to 20V
Zero elevation	0 to 200 %	-100 to +200 %




Terminal Assignments



1	INPUT	(A)
2	N.C.	
3	INPUT	(±)
4	N.C.	
5	N.C.	
6	N.C.	
7	OUTPUT- 1	(+)
8	GND	
9	OUTPUT- 1	(-)
10	SUPPLY	(L+)
11	SUPPLY	(N-)


Note: For single-output type, OUTPUT2 is N.C.

Block Diagram



Note: Digital computing circuit is added for the input/output suffix codes other than "A" and "6"

External Dimension



The information covered in this document is subject change without notice for reasons of improvements in quality and/or performance.

